



**SECTION 1: IDENTIFICATION**

PRODUCT IDENTIFIER

Product Name : Ethyl Acetate

Product Code : B-3808

Intended Use(s) : Remover for skin adhesive

CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET

Factor II, Incorporated PO  
Box 1339  
5642 White Mountain Ave Lakeside AZ  
85929  
928-537-8387  
800-332-8688  
[www.factor2.com](http://www.factor2.com)  
[sales@factor2.com](mailto:sales@factor2.com)

EMERGENCY TELEPHONE NUMBERS

Factor II, Incorporated 1 928 368 7502

**SECTION 2: HAZARD(S) IDENTIFICATION**

**2.1 Classification of the substance or mixture**

**GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

**2.2 GHS Label elements, including precautionary statements**

Pictogram



**Signal word** Danger

**Hazard statement(s):**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.



**Precautionary statement(s)**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ eye protection/ face protection.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice/ attention.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/ container to an approved waste disposal plant.

**2.3 Hazards not otherwise classified (HNOC) or not covered by GHS**

Repeated exposure may cause skin dryness or cracking.

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

**3.1 Substances**

- Formula:** C4H8O2
- Molecular weight:** 88.11 g/mol
- CAS-No.:** 141-78-6
- EC-No.:** 205-500-4
- Index-No.:** 607-022-00-5
- Registration number:** 01-2119475103-46-XXXX

**Hazardous components**

Component	Classification	Concentration
<b>Ethyl acetate</b>	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336	<= 100 %



For the full text of the H-Statements mentioned in this Section, see Section 16.

## **SECTION 4: FIRST-AID MEASURES**

### **4.1 Description of first aid measures**

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### **If inhaled**

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### **In case of skin contact**

Wash off with soap and plenty of water. Consult a physician.

#### **In case of eye contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### **If swallowed**

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### **4.2 Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### **4.3 Indication of any immediate medical attention and special treatment needed**

No data available

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### **5.2 Special hazards arising from the substance or mixture**

No data available

### **5.3 Advice for firefighters**

Wear self-contained breathing apparatus for firefighting if necessary.

### **5.4 Further information**

Use water spray to cool unopened containers.



**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

**6.2 Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

**6.3 Methods and materials for containment and cleaning up**

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

**6.4 Reference to other sections**

For disposal see section 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

For precautions see section 2.2.

**7.2 Conditions for safe storage, including any incompatibilities**

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

**8.1 Control parameters**

**Components with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
Ethyl acetate	141-78-6	TWA	400.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Respiratory Tract irritation Eye irritation		
		TWA	400.000000 ppm 1,400.000000 mg/m3	USA. NIOSH Recommended Exposure Limits



		TWA	400.000000 ppm 1,400.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in mg/m3 is approximate.		
		TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Upper Respiratory Tract irritation Eye irritation		
		TWA	400 ppm 1,400 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	400 ppm 1,400 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in mg/m3 is approximate.		
		PEL	400 ppm 1,400 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

**Derived No Effect Level (DNEL)**

Application Area	Exposure routes	Health effect	Value
Workers	Inhalation	Acute systemic effects	1468 mg/m3
Workers	Inhalation	Acute local effects	1468 mg/m3
Workers	Skin contact	Long-term systemic effects	63mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	734 mg/m3
Workers	Inhalation	Long-term local effects	734 mg/m3
Consumers	Inhalation	Acute local effects, Acute systemic effects	734 mg/m3
Consumers	Skin contact	Long-term systemic effects	37mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	367 mg/m3
Consumers	Ingestion	Long-term systemic effects	4.5mg/kg BW/d
Consumers	Inhalation	Long-term local effects	367 mg/m3

**Predicted No Effect Concentration (PNEC)**

Compartment	Value
Soil	0.24 mg/kg
Marine water	0.026 mg/l
Fresh water	0.26 mg/l
Marine sediment	0.125 mg/kg
Fresh water sediment	1.25 mg/kg

**8.2 Exposure controls****Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.



## Personal protective equipment

### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

### Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 113 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail [sales@kcl.de](mailto:sales@kcl.de),

test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be

selected according to the concentration and amount of the dangerous substance at the specific workplace.

### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

- |                                 |   |
|---------------------------------|---|
| a) Appearance                   | Form: clear, liquid<br>Colour: colourless |
| b) Odour                        | No data available                         |
| c) Odour Threshold              | No data available                         |
| d) pH                           | No data available                         |
| e) Melting point/freezing point | -84.0 °C (-119.2 °F)                      |



<b>f) Initial boiling point and boiling range</b>	76.5 - 77.5 °C (169.7 - 171.5 °F) - lit.
<b>g) Flash point</b>	-3.0 °C (26.6 °F) - closed cup No data available
<b>h) Evaporation rate</b>	No data available
<b>i) Flammability (solid, gas)</b>	No data available
<b>j) Upper/lower flammability or explosive limits</b>	Upper explosion limit: 11.5 %(V) Lower explosion limit: 2.2 %(V)
<b>k) Vapour pressure</b>	97.3 hPa (73.0 mmHg) at 20.0 °C (68.0 °F)
<b>l) Vapour density</b>	No data available
<b>m) Relative density</b>	0.90 g/cm <sup>3</sup> at 20 °C (68 °F)
<b>n) Water solubility</b>	soluble
<b>o) Partition coefficient: n- octanol/water</b>	log Pow: 0.73
<b>p) Auto-ignition temperature</b>	427.0 °C (800.6 °F)
<b>q) Decomposition temperature</b>	No data available
<b>r) Viscosity</b>	No data available
<b>s) Explosive properties</b>	No data available
<b>t) Oxidizing properties</b>	No data available

**9.2 Other safety information**

Surface tension 24.0 mN/m at 20.0 °C (68.0 °F)

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity**

No data available

**10.2 Chemical stability**

Stable under recommended storage conditions.

**10.3 Possibility of hazardous reactions**

Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Heat, flames and sparks.

**10.5 Incompatible materials**

Strong oxidizing agents

**10.6 Hazardous decomposition products**

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity**

LD50 Oral - Rat - 5,620 mg/kg

LC50 Inhalation - Mouse - 2 h - 45,000 mg/m<sup>3</sup>



LD50 Dermal - Rabbit - > 18,000 mg/kg  
No data available

**Skin corrosion/irritation**

Skin - Rabbit

Result: Mild skin irritation  
(OECD Test Guideline 404)

**Serious eye damage/eye irritation Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

This product is or contains a component that is not classifiable as to its carcinogenicity based on its **IARC, ACGIH, NTP, or EPA** classification.

**IARC:** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**NTP:**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**OSHA:**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Reproductive toxicity**

No data available

No data available

**Specific target organ toxicity - single exposure**

May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**Additional Information**

RTECS: AH5425000

Inhalation of high concentrations may cause:, Headache, Drowsiness, Dizziness, Vomiting, narcosis, anemia, Central nervous system depression

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence



**SECTION 12: ECOLOGICAL INFORMATION**

**12.1 Toxicity**

**Toxicity to fish**

LC50 - Oncorhynchus mykiss (rainbow trout) - 350.00 - 600.00 mg/l - 96 h

LC50 - Pimephales promelas (fathead minnow) - 220.00 - 250.00 mg/l - 96 h

**Toxicity to daphnia and other aquatic invertebrates**

EC50 - Daphnia magna (Water flea) - 2,300.00 - 3,090.00 mg/l - 24 h

**Toxicity to algae**

LC50 - Daphnia magna (Water flea) - 560 mg/l - 48 h

EC50 - Algae - 4,300.00 mg/l - 24 h

EC50 - SELENASTRUM - 1,800.00 - 3,200.00 mg/l - 72 h

**12.2 Persistence and degradability**

**Biodegradability**

Result: 79 % - Readily biodegradable  
(OECD Test Guideline 301D)

**12.3 Bioaccumulative potential**

Bioaccumulation - 3 d

Bioconcentration factor (BCF): 30

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

**12.6 Other adverse effects**

No data available

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

**Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging**

Dispose of as unused product.



**SECTION 14: TRANSPORT INFORMATION**

**DOT (US)**

UN number: 1173      Class: 3      Packing group: II  
Proper shipping name: Ethyl acetate  
Reportable Quantity (RQ): 5000 lbs  
Poison Inhalation Hazard: No

**IMDG**

UN number: 1173      Class: 3      Packing group: II EMS-No: F-E, S-D  
Proper shipping name: ETHYL ACETATE

**IATA**

UN number: 1173      Class: 3      Packing group: II  
Proper shipping name: Ethyl acetate

**SECTION 15: REGULATORY INFORMATION**

**SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**SARA 311/312 Hazards**

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**Massachusetts Right To Know Components**

	CAS-No.	Revision Date
Ethyl acetate	141-78-6	1993-04-24

**Pennsylvania Right To Know Components**

	CAS-No.	Revision Date
Ethyl acetate	141-78-6	1993-04-24

**New Jersey Right To Know Components**

	CAS-No.	Revision Date
Ethyl acetate	141-78-6	1993-04-24

**California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**SECTION 16: OTHER INFORMATION**

**Full text of H-Statements referred to under sections 2 and 3.**

Eye Irrit. Eye irritation  
Flam. Liq. Flammable liquids



## Factor II, Incorporated

The Art, Science and Technology of  
Silicones and Prosthetics...

## \*Safety Data Sheet\*

B-3808

Date of Issue: 09/19/2014

Revision Date 03/07/2017

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
STOT SE Specific target organ toxicity - single exposure

### HMIS Rating

Health hazard:	2
Chronic Health	*
Hazard: Flammability:	3
Physical Hazard	0

### NFPA Rating

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	0

### PATENT WARNING:

Factor II Technology disclaims any expressed or implied warranty against the infringement of any patent. Factor II does not warrant that the use or sale of the products described herein will not infringe the claims of any U.S. patents or other country's patents covering the product itself or the use in combination with other products or in the operation of any process.

### WARNINGS ABOUT PRODUCT SAFETY:

Factor II technology believes that the information and data contained herein is accurate and reliable; however, it is the user's responsibility to determine suitability and safety of use for these materials.

Factor II cannot know the specific requirements of each application and hereby makes the user aware that it has not tested or determined that these materials are suitable or safe for any application. It is the user's responsibility to adequately test and determine the safety and suitability for their application. Factor II makes no warranty concerning fitness for any use or purpose. There has been no testing done by Factor II to establish safety of use in any medical application. Factor II has tested this material only to determine if the product meets the applicable specification. When considering the use a Factor II product in a particular application, you should review the latest Material Safety Data Sheets and contact Factor II for any questions about product safety information you may have.

**IT IS RECOMMENDED THAT THE PURCHASER THOROUGHLY TEST ANY APPLICATION PRIOR TO FULL SCALE PRODUCTION OR COMMERCIALIZATION. INFORMATION CONTAINED IN THIS TECHNICAL PROFILE SHOULD NOT BE TAKEN AS INDUCEMENT TO FRINGE ANY PATENT. FACTOR II WARRANTS ONLY THAT ITS PRODUCTS MEET ITS SPECIFICATIONS. THERE IS NO WARRANTY OF MERCHANTABILITY OF FITNESS FOR USE OR ANY OTHER WARRANTIES EXPRESS OR IMPLIED. FACTOR II MAKES NO GUARANTEE OF SATISFACTORY RESULTS**

### ***DISCLAIMER / STATEMENT OF LIABILITY:***

*This is to certify that the above designated material has been tested and did comply with the listed specifications (with listed exceptions) when supplied in original container. The material is subject to the conditions listed on the invoice. The above is a copy of information on file. The lot acceptance data are available for examination. This is a computer-generated document that is valid without a signature. The information above is supplied in good faith and, to the best of our knowledge, is based on available sources believed to be reliable and accurate. This document and any information provided herein are for your guidance only. The use by the requestor is beyond Factor II control; therefore, the responsibility for appropriate and safe use of the above information lies with the End user. Factor II shall not be responsible for any misuse and/or misapplication of the information in this document. Factor II is a distributor of this product not the manufacture. Factor II will warrant this product 6-months from the ship date, some restrictions apply.*