Factor II Inc. encourages the end user to read this document entirely and understand all sections of this SDS sheet prior to use. There is important information regarding this product. The end user is expected to follow all precautions outlined in this SDS.

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER

Product Name : Monopoly Syrup

Product Code : J-305

Intended Use(s) : For professional use only

CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET

Factor II, Incorporated
5642 White Mountain Ave
PO Box 1339
Lakeside AZ 85929
928-537-8387
www.factor2.com
sales@factor2.com

EMERGENCY TELEPHONE NUMBERS

928- 368-7502

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification

Hazard class Flammable liquids, Category 2

Hazard Pictogram(s)

Signal word Danger

Hazard statement(s)
H225 Highly flammable liquid and vapor
H240 Heating may cause an explosion
H317 May cause and allergic skin irritation

H319 Causes serious eye irritation

Precautionary statement(s)

Prevention

P210 Keep away from heat/sparks/open flame/hot surfaces, no smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion-proof electrical/ventilating/lighting equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P261 Avoid breathing mist or vapors
P271 Use only outdoors or in a well-ventilated area
P272 Contaminated work clothing should not be allowed out of the workplace
P280 Wear protective gloves/protective clothing/eye protection/ face protection Response
P302 + P352 +P314 + P362 IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. Seek medical attention if irritation persists.
P304 + P340 + P314 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if you feel unwell.
P305 + P351 + P338 + P314 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if you feel unwell.
P301 + P311 +P322 IF SWALLOWED: Give one to two glasses of water if victim is alert. Call a POISON CENTER or doctor/physician. Storage
P401 + P404 + P235 + P410 + P412 Store in a cool, dry place away from heat, sparks, flame and direct sunlight. Do not expose to temperatures exceeding 70°F (21°C). Disposal
P501 Dispose of contents/container to an approved waste disposal plant.

Other hazard(s)

Static-accumulating flammable liquid.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Concentration (%)
Particulates NOC	NE	< 1
Residual monomers	80-62-6	< 99

The specific chemical identities have been withheld as a trade secret.

SECTION 4: FIRST-AID MEASURES

In the case of accident or if you feel unwell, see medical attention immediately. When symptoms persist, or in all cases of doubt, seek medical attention.

First-aid instructions by relevant routes of exposure include:

Inhalation Remove victim to fresh air. Give oxygen or artificial respiration if not breathing. Seek medical attention if symptoms persist.

Skin contact Immediately wash thoroughly with soap and water while removing contaminated clothing and shoes. Seek medical attention. Wash clothing and thoroughly clean shoes before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes, including under eyelids. If worn and easy to do, remove contact lenses. Seek medical attention.

Ingestion DO NOT induce vomiting. Give two glasses of water to drink. Seek medical attention immediately.

Most important symptoms and effects, both acute and delayed
Causes serious eye irritation. May cause mild skin irritation.

First aid responders First aid responders should pay attention to self-protection and use the recommended personal protective equipment when the potential for exposure exists.

Note to physician Treat symptomatically and supportively.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable extinguishing media Alcohol foam, carbon dioxide and dry chemical

Unsuitable extinguishing media High volume water jet

Specific hazards during fire	Do not use a solid water stream as it may scatter and fighting spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Heat can cause polymerization with rapid release of energy which may rupture container explosively. Exposure to combustion products may be a hazard to health. Prevent buildup of vapors or gases to explosive concentrations.
Hazardous combustion	Oxides of carbon products
Specific extinguishing methods	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate area and eliminate sources of ignition. Use water spray to cool unopened containers. Remove undamaged containers from fire area if safe to do so.
Special protective equipment	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Firefighting equipment should be thoroughly decontaminated after use.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions and emergency procedures

Remove all sources of ignition, ventilate the area and keep upwind. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area by containment or oil barriers. Retain and dispose of contaminated wash water. Spills on porous surfaces can contaminate groundwater. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleanup procedures

Non-sparking tools should be used. Soak up with inert absorbent materials. Suppress (knock down) gases/vapors/mist with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. See Sections 13 and 15 of this SDS for information regarding certain local or national requirements.

SECTION 7: HANDLING AND STORAGE

Technical measure

Ensure all equipment is electrically grounded before beginning transfer operations. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Restrict flow velocity in order to reduce the accumulation of static electricity.

Local/total ventilation

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.

Precautions for safe handling

Do not get on skin or clothing. Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage

Keep away from food, drink and animal feeding stuffs. Keep container tightly closed and in a cool, well-ventilated place away from heat, sparks, flame and direct sunlight. Store in accordance with the particular national regulations.

Materials to avoid

Oxidizing agents, reducing agents, peroxides, acids, alkalis, amines and UV light.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

OSHA HAZARDOUS COMPONENTS					
		EXPOSURE LIMITS			
			OSHA PEL	**ACGIH TLV**	
Component Name, CAS Number			**ppm**	**mg/m3**	ppm
Particulates NOC, NE	**TWA**		**15**		**NE**
	STEL				
Residual Monomers, 80-62-6	**TWA**		**100**		**NE**
	STEL				

Engineering Controls

Processing may form hazardous compounds (see Section 10). Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.

Personal Protective Equipment Pictograms

Protective goggles. Gloves. Protective clothing, ventilation

Respiratory

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Eye/Face

Use safety goggles as a minimum when working with chemicals.

Hands

Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, clarify the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands thoroughly before breaks and at the end of workday.

Skin/Body

Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: flame retardant antistatic protective clothing. Avoid skin contact by using protective clothing (gloves, aprons, boots, etc.).

Hygiene measures

Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications,

please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear liquid
Upper/lower flammability or explosive limits	12.5 / 2.12
Odor	Acrid
Vapor pressure	28 mm Hg @ 68°F
Odor	Acrid Odor
Vapor density	3.5 @ 60°F
pH	No data available
Relative density	No data available
Melting point/freezing point	No data available
Solubility(ies)	Moderate
Initial boiling point and boiling range	214°F (101°C)
Flash point	52.7°F (11.5°C)
Evaporation rate	Not applicable
Flammability (solid, gas)	No data available
Partition coefficient n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Reactive
Chemical stability	Unstable; may polymerize at elevated temperatures.
Hazardous reactions	Highly flammable liquid and vapor. Temperatures above 70°F (21°C) can produce vapors that can mix with air and burn or be explosive. May form highly hazardous compounds. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures. Hazardous polymerization may occur.
Conditions to avoid	Heat above 70°F, flames and sparks; aging and contamination.

Incompatibilities	Oxidizing agents, reducing agents, peroxides, acids, alkalis, amines and UV light. Material has strong solvent properties and can soften paint and rubber.
Hazardous thermal	Oxides of carbon decomposition products

SECTION 11: TOXICOLOGICAL INFORMATION

Mixture Toxicity

Inhalation Toxicity 4,876mg/L

Component Toxicity

Routes of Exposure No data available

Target Organs Eyes Skin Respiratory System

Effects of Overexposure

Product Components Listed as Carcinogenic

SECTION 12: ECOLOGICAL INFORMATION

Methacrylate monomer

Toxicity to fish

LC50	Pimephales promelas (fathead minnow) 410 mg/l
Exposure time	96 h

Toxicity to aquatic invertebrates No data available

Toxicity to aquatic plants No data available

PERSISTENCE AND DEGRADABILITY No data available

BIOACCUMULATIVE POTENTIAL No data available

MOBILITY IN SOIL No data available

OTHER ADVERSE EFFECTS

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Product

This product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

Resource Conservation Recovery Act (RCRA)

When a decision is made to discard this material as supplied, And it is classified as a RCRA hazardous waste.

Waste Code D001 Ignitability

Waste from residues Dispose of in accordance with local regulations

Contaminated packaging

Dispose of as unused product. Do not re-use empty containers. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: TRANSPORT INFORMATION

US DOT

Proper shipping name	Methyl methacrylate monomer, stabilized
UN number	UN1247
Hazard class(es)	3
Packing group	II
Labels	Flammable liquids
ERG Code	129P
Marine pollutant	No

IATA and ICAO

Proper shipping name	Methyl methacrylate monomer, stabilized
UN number	UN1247
Hazard class(es)	3
Packing group	II
Labels	Flammable liquids
Packing instructions	Passenger/Cargo aircraft – 353

SECTION 15: REGULATORY INFORMATION

EPCRA - EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW

CERCLA Reportable Quantity

Ingredients	CAS Number	Component RQ (lbs)
Methyl methacrylate monomer	80-62-6	1,000

SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS Number	Component RQ (lbs)
Methyl methacrylate monomer	80-62-6	1,000

SARA 311/312 Hazards Fire hazard
Acute health hazard
Reactive hazard

SARA 302

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Methyl methacrylate monomer 80-62-6 99%

US STATE REGULATIONS

California Prop 65

This product contains no chemical(s) known in the State of California to cause birth defects or other reproductive harm.

Massachusetts Right To Know

Methyl methacrylate monomer 80-62-6 99%

New Jersey Right To Know

Methyl methacrylate monomer 80-62-6 99%

Pennsylvania Right To Know

Methyl methacrylate monomer 80-62-6 99%

Rhode Island Right To Know

Methyl methacrylate monomer 80-62-6 99%

The ingredients of this product are reported in the following inventories:

NZIoC	All ingredients listed or exempt
REACH	All ingredients (pre-) registered or exempt
TSCA	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances
AICS	All ingredients listed or exempt
IECSC	All ingredients listed or exempt
ENCS/ISHL	All components are listed on ENCS/ISHL or exempted from inventory listing
KECI	All ingredients listed, exempt or notified
PICCS	All ingredients listed or exempt

DSL All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL)

Inventories: AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16: OTHER INFORMATION

HMIS III:

Health	2 – Moderate
Flammability	3 – High
Physical Hazards	2 – Moderate

NFPA:

Health	2 – Moderate
Flammability	3 – High
Instability	2 – Moderate
Special hazard	

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER

Product Name Silicone Elastomer

Product Code A-RTV-4020 C

Intended Use(s) : For professional use only

CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET

Factor II, Incorporated
5642 White Mountain Ave
PO Box 1339
Lakeside AZ 85929
928-537-8387
www.factor2.com
sales@factor2.com

EMERGENCY TELEPHONE NUMBERS

928- 368-7502

SECTION 2: HAZARD IDENTIFICATION

Hazard Classification Not a hazardous substance or mixture according to GHS.

Label Elements

Hazard Symbol No symbol.

Signal Word No signal word.

Hazard Statement Not applicable.

Precautionary Statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Other hazards which do not result in GHS classification

Chemical compounds containing silicon - hydrogen bonds (SiH). This product may generate hydrogen gas. For further information, refer to Section 10: "Stability and Reactivity".

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Composition Comments Mixture of Polyorganosiloxanes, fillers.

SECTION 4: FIRST AID MEASURES

General information For further information refer to section 8 "Exposure-controls/ personal protection".

Ingestion Do not induce vomiting. Rinse mouth thoroughly. Get medical attention if symptoms occur.

Inhalation Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Skin Contact Wash skin thoroughly with soap and water. Get medical attention

if symptoms occur after washing.

Eye contact In the event of contact with the eyes, rinse thoroughly with clean water for at least 15 minutes. Get medical attention if irritation persists after washing.

Most important symptoms/effects, acute and delayed

Symptoms None known.

Hazards No specific recommendations.

Indication of immediate medical attention and special treatment needed

Treatment No specific recommendations.

SECTION 5: FIRE FIGHTING MEASURES

General Fire Hazards Water spray should be used to cool containers.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

Dry chemical, alcohol resistant foam or carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire. Do not use alkaline powders.

Specific hazards arising from the chemical

Product will burn under fire conditions. This product may generate hydrogen gas. Vapors may form explosive mixtures with air. For further information, refer to Section 10: "Stability and Reactivity". Hazardous Decomposition Products : formaldehyde, oxides of carbon and silica.

Special protective equipment and precautions for firefighters

Special firefighting procedures

Water spray should be used to cool containers.

Special protective equipment for fire-fighters:

Firefighters should wear standard protective equipment and a positive pressure self-contained breathing apparatus (SCBA).

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear appropriate personal protective equipment. See Section 8 of the SDS for Personal

Protective Equipment. Avoid contact with alkalis and caustic products. Eliminate all sources of ignition.

Methods and material for containment and cleaning up

Ventilate the area. Use non-sparking tools. Absorb with sand or other inert absorbent. Avoid contact with bases. Scrape up and place in appropriate vented container.

Notification Procedures

Caution: Contaminated surfaces may be slippery. For waste disposal, see Section 13 of the SDS.

Environmental Precautions

Do not allow to enter drains, sewers or watercourses.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Provide adequate ventilation if fumes or vapors are generated. Do not mix with incompatible materials. For further information, refer to Section 10: "Stability and Reactivity". Read and follow manufacturer's recommendations.

Conditions for safe storage, including any incompatibilities

Store in original vented container. Store in a cool, dry place with adequate ventilation. Keep away from incompatible materials, open flames, and high temperatures.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits None of the components have assigned exposure limits.

Appropriate Engineering Controls No special precautions.

Individual protection measures, such as personal protective equipment

General information

Provide sufficient ventilation during operations which cause vapor formation. This product can form formaldehyde vapors when heated to temperatures above 150 degrees C in the presence of air.

Eye/face protection Wear approved chemical safety glasses.

Skin Protection

Hand Protection Protective gloves are recommended.

Other Wear suitable protective clothing.

Respiratory Protection

No protection is ordinarily required under normal conditions of use and with adequate ventilation. If ventilation is insufficient, suitable respiratory protection must be provided.

Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (Based on typical material)

Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Form	Viscous
Color	Colorless
Odor	Slight odor
Odor threshold	No data available.
pH	Not applicable.
Freezing point	No data available.
Boiling Point	No data available.
Flash Point	> 392 °F (200 °C)
Evaporation rate	No data available.
Flammability (solid, gas)	No data available.
Flammability limit - upper (%)	74 %(V) Hydrogen.
Flammability limit - lower (%)	4 %(V) Hydrogen.
Vapor pressure	No data available.
Vapor density	No data available.
Relative density	1.04 (77 °F (25 °C))
Solubility(ies)	
Solubility in water	Insoluble
Solubility (other)	No data available.
Partition coefficient (n-octanol/water)	No data available.
Auto-ignition temperature	932 °F (500 °C) Hydrogen.
Decomposition temperature	No data available.
Viscosity	200 - 600 mm2/s (77 °F (25 °C))

SECTION 10: STABILITY AND REACTIVITY DATA

Reactivity No data available.

Chemical Stability	Material is stable under normal conditions.
Possibility of hazardous reactions	This product may generate hydrogen gas.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.

Incompatible Materials

A fire or explosion hazard arises because highly flammable gas (hydrogen) is released when it is in contact with: Strong oxidizers, strong bases and chemical compounds with mobile hydrogen, in the presence of metal salts and complexes.

Hazardous Decomposition Products

This product can form formaldehyde vapors when heated to temperatures above 150 degrees C in the presence of air. Thermal decomposition or combustion may liberate carbon oxides, other toxic gases or vapors and amorphous silica.
Quantity of hydrogen potentially released (l/kg of product): ~38

SECTION 11: TOXICOLOGAICAL INFORMATION

Information on likely routes of exposure

Ingestion	No data available.
Inhalation	No data available.
Skin Contact	No data available.
Eye contact	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion	No data available.
Inhalation	No data available.
Skin Contact	No data available.
Eye contact	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product	ATEmix: 2,500 mg/kg
Dermal Product	No data available.
Inhalation Product	No data available.
Repeated dose toxicity Product	No data available.
Skin Corrosion/Irritation Product	No data available.
Serious Eye Damage/Eye Irritation Product	No data available.

Respiratory or Skin Sensitization Product No data available.

Carcinogenicity Product No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
No carcinogenic components identified

Germ Cell Mutagenicity
In vitro Product No data available.

In vivo Product No data available.

Reproductive toxicity Product No data available.

Specific Target Organ Toxicity - Single Exposure Product
No data available.

Specific Target Organ Toxicity - Repeated Exposure Product
No data available.

Aspiration Hazard Product No data available.

Other effects No data available.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product No data available.

Aquatic Invertebrates Product No data available.

Chronic hazards to the aquatic environment

Fish Product No data available.

Aquatic Invertebrates Product No data available.

Toxicity to Aquatic Plants Product No data available.

Persistence and Degradability

Biodegradation Product No data available.

BOD/COD Ratio Product No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF) Product No data available.

Partition Coefficient n-octanol / water (log Kow) Product
No data available.

Mobility in soil No data available.

Other adverse effects No data available

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal instructions

Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Waste of this material should not be mixed with other waste. Provide measures such as vented bungs to ensure pressure relief in the waste container. Contaminated packages should be as empty as possible and equipped with a degassing device.

SECTION 14: TRANSPORT INFORMATION

This material is not subject to transport regulations.

Environmental hazards Not regulated.

Special precautions for user Packaging with a breathing/venting bung are FORBIDDEN for transport by air.

SECTION 15: REGULATORY INVORMATION

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):
None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

___ Acute (Immediate) __ Chronic (Delayed) __ Fire __ Reactive __ Pressure Generating

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification
None present or none present in regulated quantities.

SARA 313 (TRI Reporting)
None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)
None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):
None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65
No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act
No ingredient regulated by NJ Right-to-Know Law present.

US. Massachusetts RTK - Substance List
No ingredient regulated by MA Right-to-Know Law present.

US. Pennsylvania RTK - Hazardous Substances
No ingredient regulated by PA Right-to-Know Law present.

US. Rhode Island RTK No ingredient regulated by RI Right-to-Know Law present.

Inventory Status

US TSCA Inventory	On or in compliance with the inventory.
Canada DSL Inventory List	On or in compliance with the inventory.
EU EINECS List	On or in compliance with the inventory.
Japan (ENCS) List	On or in compliance with the inventory.
China Inv. Existing Chemical Substances	On or in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI)	On or in compliance with the inventory.
Australia AICS	On or in compliance with the inventory.
Philippines PICCS	On or in compliance with the inventory.
New Zealand Inventory of Chemicals	On or in compliance with the inventory.

SECTION 16: OTHER INFORAMTION

HMIS Hazard ID

Health	**1 - Slight**
Flammability	**1 - Slight**
Physical Hazards	**1 - Slight**
PERSONAL PROTECTION	**B – Safety Glasses and gloves**

NFPA Hazard ID

Flammability	**1 - Slight**
Health	**1 - Slight**
Reactivity	**1 - Slight**
Special Hazard	

PATENT WARNING:
Factor II Technology disclaims any expressed or implied warranty against the infringement of any patent. Factor II does not warrant that the use or sale of the products described herein will not infringe the claims of any U.S. patents or other country's patents covering the product itself or the use in combination with other products or in the operation of any process.

WARNINGS ABOUT PRODUCT SAFETY:
Factor II technology believes that the information and data contained herein is accurate and reliable; however, it is the user's responsibility to determine suitability and safety of use for these materials. Factor II cannot know the specific requirements of each application and hereby makes the user aware that it has not tested or determined that these materials are suitable or safe for any application. It is the user's responsibility to adequately test and determine the safety and suitability for their application. Factor II makes no warranty concerning fitness for any use or purpose. There has been no testing done by Factor II to establish safety of use in any medical application. Factor II has tested this material only to determine if the product meets the applicable specification. When considering the use a Factor II product in a particular application, you should review the latest Material Safety Data Sheets and contact Factor II for any questions about product safety information you may have.

IT IS RECOMMENDED THAT THE PURCHASER THOROUGHLY TEST ANY APPLICATION PRIOR TO FULL SCALE PRODUCTION OR COMMERCIALIZATION. INFORMATION CONTAINED IN THIS TECHNICAL PROFILE SHOULD NOT BE TAKEN AS INDUCEMENT TO FRINGE ANY PATENT. FACTOR II WARRANTS ONLY THAT ITS PRODUCTS MEET ITS SPECIFICATIONS. THERE IS NO WARRANTY OF MERCHANTIBILITY OF FITNESS FOR USE OR ANY OTHER WARRANTIES EXPRESS OR IMPLIED. FACTOR II MAKES NO GUARANTEE OF SATISFACTORY RESULTS

DISCLAIMER / STATEMENT OF LIABILITY:

This is to certify that the above designated material has been tested and did comply with the listed specifications (with listed exceptions) when supplied in original container. The material is subject to the conditions listed on the invoice. The above is a copy of information on file. The lot acceptance data are available for examination. This is a computer-generated document that is valid without a signature. The information above is supplied in good faith and, to the best of our knowledge, is based on available sources believed to be reliable and accurate. This document and any information provided herein are for your guidance only. The use by the requestor is beyond Factor II control; therefore, the responsibility for appropriate and safe use of the above information lies with the End user. Factor II shall not be responsible for any misuse and/or misapplication of the information in this document. Factor II is a

distributor of this product not the manufacure. Factor II will warrant this product 6-months from the ship date, some restrictions apply.